

CLN 801

Tension (V)				Tension (V)			
-28	19	1	V1	20			
-19	17	1,14	V1	18			
-21	15	1,23	-22	16			
-23	13	1,23	-24	14			
-25	11	1,23	-26	12			
-18	9	1,15	V2	10			
-11	7	1,27	V2	8			
-13	5	1,24	-12	6			
-15	3	0,8	-14	4			
-17	1	0,63	-16	2			

CLN 802

Tension (V)				Tension (V)			
-19	19	1,11	V3	20			
-1G	17	1,18	V3	18			
-1E	15	1,22	-1F	16			
-1C	13	0,69	-1D	14			
-1A	11	0,62	-1B	12			
-29	9	1,22	V4	10			
-2G	7	1,29	V4	8			
-2E	5	0,68	-2F	6			
-2C	3	0,73	-2D	4			
-2A	1	0,625	-2B	2			

carte alimentation
BN44 00362A

input 100 - 240 v 50/60 hz 2,5A

output

voltage

current

STBY: 5 2V / 0,1A

12V: 12,8V/3,5A

5 3: 5,3 V /3,5A

Vamp: 18V /0,55A

Lead driver output : 32V/840 mA

Model: PSLF251B02A

CNL 803

Tension (V)				Tension (V)			
SERIAL DATA	13	0,0428	SERIAL STT	14			
V SYNC IN	11	0,0428	GND	12			
SERIAL END	9	0,0426	SERIAL UHR	10			
NC	7		CONTACT	8			
GND	5	0	NC	6			
EXT DP	3	3,31	SCL LED	4			
SDA LED	1	3,3	SW RESET	2			

CNM 801

Tension (V)				Tension (V)			
Vamp	17	18,22	PS/ON	18			
Vamp	15	18,22	STBY	16			
5,3	13	5,259	5,3	14			
5,3	11	5,259	GND	12			
GND	9	0	GND	10			
GND	7	0	NC	8			
12V	5	12,805	NC	6			
12V	3	12,804	BL/ON	4			
12V	1	12,804	NC	2			